

# PreTagg<sup>®</sup> ShadowRemover

## Technical Data Sheet

### Applications:

PreTagg<sup>®</sup> ShadowRemover is an alkaline solvent-based graffiti remover. PreTagg<sup>®</sup> ShadowRemover is extremely suitable for removing stubborn stains or shadow marks from unpainted porous surfaces such as clinkers, masonry, concrete or brick. PreTagg<sup>®</sup> ShadowRemover can also be used on various types of plastic and metal such as zinc and aluminium.

It is always advisable to perform a test to check its compatibility with the surface and prevent damage.

### Instructions for use:

1. Make sure the surface is dry before applying PreTagg<sup>®</sup> ShadowRemover. Test for possible reactions with the surface by performing a small test in an inconspicuous place.
2. Apply the PreTagg<sup>®</sup> ShadowRemover to the graffiti or shadow mark with a scrubbing brush or paintbrush. Use a scrubbing brush and make circular movements to work the product in properly.
3. Then let PreTagg<sup>®</sup> ShadowRemover soak in. The time this takes will depend on the surface, the type of graffiti, etc. On porous surfaces, apply enough product to fully saturate the surface.
4. Start removing the graffiti from the bottom upwards and always a small part at a time.
5. Remove with high pressure and hot water.
6. Multiple treatments may be required. Then dry the surface between treatments.

### Product usage:

Depending on the kind of material, condition and the porosity of the treated surface 3 - 8 m<sup>2</sup> per liter.

The project usage needs to be determinate by placing a reference test on the surface.

### Considerations during application:

- Always apply the product to a small test area of the surface to be treated in order to determine the aesthetic and technical result.

### Special advantages:

- PreTagg<sup>®</sup> ShadowRemover is easy to use.
- PreTagg<sup>®</sup> ShadowRemover quickly and effectively removes shadow marks or graffiti.
- PreTagg<sup>®</sup> ShadowRemover is suitable for many types of surfaces.

### Specifications:

|              |                        |
|--------------|------------------------|
| Colour:      | Colourless             |
| Odour:       | Characteristic         |
| pH:          | +13                    |
| Flash point: | 32 degrees Celsius     |
| Density:     | 0.97 g/cm <sup>3</sup> |

### Hazard symbols and H & P statements (CLP):



GHS02  
Danger

GHS05

H-statements: H226 - Flammable liquid and vapour.  
H314 - Causes severe skin burns and eye damage.

P-statements: P210 - Keep away from heat, hot surfaces, sparks, open flames. No smoking.  
P233 - Keep container tightly closed.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.

### Packaging and industrial waste:

Treat as industrial waste in accordance with the applicable regulations. Collect process water in accordance with the applicable local regulations.

PreTagg<sup>®</sup> ShadowRemover is part of our PreClean<sup>®</sup>, PreCare<sup>®</sup>, PreTagg<sup>®</sup> and PreSpec<sup>®</sup> product range, developed to clean and preserve all types of construction materials. For specific questions and applications or to consult the up-to-date TDS and MSDS sheets, please visit our website [www.ccpi.com](http://www.ccpi.com)

This information is based on laboratory tests and practical experience. **For application and use, please adhere strictly to the descriptions in the technical product information sheets and MSDS sheets.** We do not accept any liability for any advice provided by us. The application, use and handling of the products are the sole responsibility of the user.

Publication date: 27th of June 2019